




产品概述 INTRODUCTION

B-OMR带制动器液压马达是由OMR摆线马达和多片式摩擦制动器组合而成,本马达自带梭阀,内置控制油路,结构紧凑,径向尺寸小,具有体积小,重量轻,使用安装方便等特点。适用于建筑、船舶、起重运输、港口、矿山、冶金和其他工程机械行业等设备中。

B-OMR are OMR orbit hydraulic motor with multi-disc brake. There are shuttle valve and inner hydraulic control system. It has small volume, short radial dimension, low weight and easy to install. It's widely applied in construction machinery, shipping machinery, cranes, mining, port, metallurgical industry, etc.

● 型号意义 ORDERING CODE



- 1、马达排量 Displacement
- 2、输出轴型式 Output shaft  
P1- 标准平键 Standard flat key    H1- 标准花键 Standard spline key
- 3、安装法兰 Mounting Flange
- 4、油口 Ports
- 5、特殊要求 Special Features

● 技术参数 TECHNICAL DATA

型号 Type	排量 Displacement ml/r	最大工作压力 Max.pressure Mpa	最大工作扭矩 Max.torque N.m	转速范围 Speed rangee	制动器开启压力 Releasing pressure Mpa	制动扭矩 Brake torque N.m	配用马达 Associated motor	重量 Weight kg	长度 L Length mm
B-OMR-80	80.5	14	152	20-500	1.2	265	OMR-80		248
B-OMR-100	100.5	14	194	20-450	1.2	265	OMR-100		252
B-OMR-125	126.3	14	237	20-400	1.2	265	OMR-125		256
B-OMR-160	160.8	14	310	20-300	2.0	400	OMR-160		262
B-OMR-200	200.9	14	369	20-250	2.0	400	OMR-200		269
B-OMR-250	252.6	11	380	15-200	2.0	400	OMR-250		278
B-OMR-315	321.5	9	380	15-160	2.0	400	OMR-315		290

● B-OMR-80(80-315) P1(H1) A Y 外形安装图 I nst all ati on

